



KE

Product number	Standard dimensions mm								
	A	B	H	E	F	P	h	d	t
KE-25	76	20	25	40	20	60	17	7	2.3
KE-30	105	30	30	50	30	85	22	9	3.2
KE-40	135	40	40	70	40	110	30	11	3.2
KE-50	165	50	50	90	50	135	38	14	4.5
KE-60	195	60	60	110	60	165	44	14	6

Product number	Support load in Z direction N {kgf}	Permissible load N {kgf}			Spring constant in Z direction N/mm {kgf/cm}	Spring constant ratio of X direction to Z direction	Spring constant ratio of Y direction to Z direction
		Z direction	X direction	Y direction			
KE-25	~ 98 {10}	150 { 15}	150 { 15}	440 { 45}	44 { 45}	1.00	4.0
KE-30	~180 {18}	340 { 35}	340 { 35}	1030 {105}	103 {105}	0.72	4.0
KE-40	~390 {40}	780 { 80}	780 { 80}	2000 {200}	140 {140}	0.83	4.1
KE-50	~540 {55}	1100 {110}	1100 {110}	2700 {280}	150 {150}	0.78	4.2
KE-60	~740 {75}	1500 {150}	1500 {150}	3600 {370}	180 {180}	0.74	3.8

The elastomer is natural rubber.